

## **Synergy**

## 15 YEAR WARRANTY CSIRO TESTED Consolidator/Penetrating Sealer

**SYNERGY** is a world class combination consolidator and penetrating sealer specially formulated for superior stain and salt protection around swimming pools. **SYNERGY** is suitable for internal, external, domestic and commercial surfaces and will prevent permanent staining from most common spills.

To minimize the effects of salt attack **ENVIRONEX** recommends installing a 40mm overflow pipe located approximately 150mm beneath the pool coping. This will remove the chance of the coping being regularly submersed in the corrosive pool water environment.



Always wear Personal Protective Equipment (PPE) – A minimum requirement of Safety Glasses, Gloves & Boots. Damage to clothing may occur.

- Do not seal under 10°C or over 30°C.
- Apply a minimum of 2 coats of SYNERGY to a clean dry surface with an ENVIRONEX LAMBSWOOL
   APPLICATOR or ENVIRONEX VITON SEAL SPRAYER. SYNERGY may take 2 to 3 days to dry.
   ENVIRONEX recommend dip sealing your coping pavers/tiles with SYNERGY. Porous masonry will require more coats (3-5) of SYNERGY to provide adequate protection. Allow minimum 7 days curing.
- Only use **REFRESH** pH neutral detergent for daily or weekly maintenance.
- Not suitable for Bluestone.
- **ENVIRONEX** recommend resealing the pool surrounds every 2-3 years to assist in prevention of Salt Attack.
- Always test first.



